

RECEIVED

09856745.092401

JUL 28 2000

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F16J 1/16		A1	(11) International Publication Number: WO 00/34696
			(43) International Publication Date: 15 June 2000 (15.06.00)
(21) International Application Number: PCT/US99/29395		[US/US]; 7620 North County Road 400 West, Scipio, IN 47273 (US). KLEPSEY, Cheryl [US/US]; 3282 N. Meadow Drive, Hope, IN 47246 (US).	
(22) International Filing Date: 10 December 1999 (10.12.99)		(74) Agents: COLE, Troy, J. et al.; Woodard, Emhardt, Naughton, Moriarty & McNett, Suite 3700, Bank One Center/Tower, 111 Monument Circle, Indianapolis, IN 46204 (US).	
(30) Priority Data: 09/210,001 11 December 1998 (11.12.98) US		(81) Designated States: BR, MX, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Application US 09/210,001 (CIP) Filed on 11 December 1998 (11.12.98)		Published With international search report. With amended claims.	
(71) Applicant (for all designated States except US): CUMMINS ENGINE COMPANY, INC. [US/US]; 500 Jackson Street, Columbus, IN 47201 (US).		Date of publication of the amended claims: 20 July 2000 (20.07.00)	
(72) Inventors; and (75) Inventors/Applicants (for US only): LUEHRMANN, Mark, G. [US/US]; 3243 North Meadow Drive, Hope, IN 47246 (US). RUPP, Mary, E. [US/US]; 9223 South State Road 3, Greensburg, IN 47240 (US). O'LEARY, Mark, D. [US/US]; 9477 West County Road 25 East, Seymour, IN 47274 (US). PIRANER, Ilya, L. [US/US]; 6064 Acorn Drive, Columbus, IN 47201 (US). MILLER, John, M. [US/US]; 4235 Sharp Lane, Columbus, IN 47201 (US). MCNULTY, William, D.			

(54) Title: CONNECTING ROD WITH PROFILED BORE FOR INCREASED LOAD CAPABILITY

(57) Abstract

An engine cylinder piston connecting rod subassembly, for use in an engine, includes a piston (53), a piston pin (52) and a connecting rod (51). The connecting rod has a piston end portion with a piston pin bore (62). The piston pin is inserted through the piston pin bore and oppositely disposed portions of the piston, for securing the piston and the connecting rod together. Opposite ends of the piston pin bore are machined or profiled with relief portions (60, 61), to allow for piston pin deflection and thereby maximize the load carrying capacity, by providing a greater area of contact. The relief portions can be a curved surface (65) machined as part of the bore, or a plurality of end-to-end angled frustoconical surfaces (66a, 66b, 66c). The relief portions are shaped to correspond to the shape of the corresponding piston pin when under load during normal engine operation.

